



**Hydraulic and
Electronic Division**



PG - PRESSURE GAUGES

1
2
3
4
5
6
7
PG 25 1 S - NB - 200/3000 - C

1	Series
PG	General, Dual Scale
PGS	All Stainless
VG	Vacuum Gauge

2	Dial Size
15	1½"
25	2½"
40	4"

3	Mounting
1	Bottom Stem
5	Back Stem
7	Panel (3-hole)
9	U-clamp

4	Liquid
S	100% silicone (-45° to 65°C)
G	100% glycerin (-15° to 65°C)
D	Dry

5	Stem Threads
NB	NPT ¼"
ND	NPT ½"

6	Pressure Range (bar / psi)
2/30	0-2 bar, 0-30 psi
4/60	0-4 bar, 0-60 psi
7/100	0-7 bar, 0-100 psi
10/150	0-10 bar, 0-150 psi
14/200	0-14 bar, 0-200 psi
20/300	0-20 bar, 0-300 psi
35/500	0-35 bar, 0-500 psi
40/600	0-40 bar, 0-600 psi
70/1000	0-70 bar, 0-1000 psi
100/1500	0-100 bar, 0-1500 psi
140/2000	0-140 bar, 0-2000 psi
160/2300	0-160 bar, 0-2300 psi
200/3000	0-200 bar, 0-3000 psi
250/3500	0-250 bar, 0-3500 psi
280/4000	0-280 bar, 0-4000 psi
350/5000	0-350 bar, 0-5000 psi
400/6000	0-400 bar, 0-6000 psi
600/9000	0-600 bar, 0-9000 psi
700/10000	0-700 bar, 0-10000 psi

7	Logo
H	Hystar
C	Canimex