



ELECTRONIC COMPONENTS

JUNCTION BOXES

WK02-08

	WK02-08
I/O	Up to 9 outputs, dump option available
Receiver	MINI directly mounted on WK box
Protection	IP65
Wiring	2.2m cable with molded DIN connector (with LED and VDR), bare end 3m battery wire
Physical	160.0 mm x 88.9 mm x 88.9 mm (6.3"H x3.5"W x3,5"D)



JUNCTION BOXES

WK10-12

	WK10-12
I/O	From 10 to 13 outputs, dump option available
Receiver	VC-93, VC-134 connected with mating harness
Protection	IP65
Wiring	2.2m cable with molded DIN connector (with LED and VDR), bare end 3m battery wire
Physical	200.7 mm x 119.4 mm x 88.9 mm (7.9"H x4.7"W x3,5"D)



JUNCTION BOXES

WK14-20

	WK14-20
I/O	From 14 to 20 outputs, dump option available
Receiver	VC-93, VC-134 connected with mating harness
Protection	IP65
Wiring	2.2m cable with molded DIN connector (with LED and VDR), bare end 3m battery wire
Physical	241.3 mm x 160.0 mm x 88.9 mm (9.5"H x 6.3"W x 3.5"D)



ELECTRONIC TIMER

TIM

- LED display
- From 1 second to almost 100 hours
- Long service life
- AC/DC voltage (7-36V, 110-240V)



CONNECTOR

C

- Wide range of connectors
- ISO 4400 DIN black or translucent connectors
- Deutsch DT and DTM connectors
- AMP or PACKARD connectors
- AC or DC voltage
- With or without LED
- Rectifier available
- IP67 DIN connectors with LED available



CONNECTOR WITH CABLES

CV AND CW

- With red or green LED and VDR
- 10A nominal current
- 250 VAC or 300 VDC working voltage
- Cable length of 1,5 ft, 3 ft, 6 ft, 10 ft or 16 ft
- IP65

