



# SPEED INCREASERS SPEED REDUCERS

## SPEED INCREASERS AND SPEED REDUCERS

### MB - SPEED INCREASERS

- Aluminum or cast-iron housing
- Connection from hydraulic pump to tractor
- 540 RPM or 1000 RPM input speed
- Male or quick-disconnect input shaft
- Double-input or splitter boxes

Type	Input configuration	HP at 540 RPM	Ratio
MB20	M6, QD6	13	1,5-2-2,5-3-3,5-3,8
MB30	M6, QD6, M6/M6	27	1-1,5-2-2,5-3-3,5-3,8
MBA30	M6, QD6, QD20, QD21	27	1-1,5-2-2,5-3-3,5-3,8
MB30D	M6, QD6	48	1-1,5-2-2,5-3-3,5-3,8
MB35D	M6, QD6	60	1-1,5-2-2,5-3-3,5-3,8-4-4,8
MB40D	M6, QD6	100	1-2-2,5-3-3,8
MLT	M6, QD6	55	2-2,5-3,1-3,7
MBF32	M6, QD6, QD20, QD21	50	1-1,5-2-2,5-3-3,5-3,8
MBF42	M6, QD6, QD20, QD21	95	2-2,5-3,2-3,7
MBFB	M6	65	2,0-2,5-3-3,5-3,8
MBFE	M6	65	2-2,5-3-3,5-3,8



## SPEED INCREASERS AND SPEED REDUCERS

### RB - SPEED REDUCERS

- Aluminum or cast-iron housing
- SAE "A" input flange
- 1" 6-spline input shaft (standard)

Type	HP rated	Ratio
RB20	13	1,5-2-2,5-3-3,5-3,8
RB30	27	1,5-2-2,5-3-3,5-3,8
RBFA22	24	1,5-2-2,5-3-3,5-3,8
RBFA33	65	2-2,5-3

