



# TANK ACCESSORIES

## TANK ACCESSORIES

### STEEL FILLER BREATHERS

The Canimex tank accessories program introduces a complete range of components with unique characteristics to keep the fluid in optimal condition.



## TANK ACCESSORIES

### BH

- Aluminum die-cast construction
- Black powder coated option
- 40 $\mu$ m (standard) / 10 $\mu$ m (optional)
- Air flow of up to 25 cfm (750 lpm)
- Dipstick available

Series	Threads NPT	Filtration $\mu$
BH-45	3/8 ; 1/2	40
BH-80	3/4 ; 1	40
BH-110	1-1/2	10
BH-145	2	10
BH-185	2-1/2	10



## TANK ACCESSORIES

## BH...A

- Aluminum die-cast construction
- 40µm (standard) / 10µm (optional)
- Air flow of up to 25 cfm (750 lpm)
- Dipstick (optional)

Series	Threads	Filtration µ
BH-65	NPT 1/2	40
BH-80	NPT 1-1/4 ; SAE 20	40
BH-110	SAE 20	40



## TANK ACCESSORIES

## BH...AH

- Sturdy aluminum die-cast construction
- Filtration SS 100 mesh (standard)
- For rugged application
- Dipstick (optional)

Series	Threads NPT
BH-45	3/8 ; 1/2 ; 3/4
BH-80	1-1/4
BH-90	2

## TANK ACCESSORIES

## BHP

- Sturdy construction (ABS)
- Splash guard (standard)
- Filtration rating of 40µm
- Suitable for miniature power packs
- Dipstick (optional)

Series	Threads NPT
BHP-35	3/8
BHP-40	1/2
BHP-45	3/4
BHP-50	1
BHP-72	1-1/4



## TANK ACCESSORIES

## BHM

- Plastic breather for mobile applications
- Filtration rating of 10µm (standard)
- Air flow up to 25 cfm (750 lpm)
- Rugged nylon housing
- Filler strainer
- Splash guard feature (standard)

Series	Threads NPT
BHM-120	1-1/4



## TANK ACCESSORIES

## SFB

- Easily replaceable spin-on element
- Cast aluminum housing
- Alternative to standard breather
- Flange and screw type mounting
- Filtration of up to 10 and 25µm
- For dusty ambient conditions

Series	Type
SFB20	Flanged or threaded
SFB30	Flanged or threaded

## TANK ACCESSORIES

## HY



- Chrome-plated steel cap
- Black powder coated finish option
- Filtration rating of 40µm (standard) / 10µm (optional)
- Air flow of up to 25 cfm (750 lpm)
- Metal strainer (standard)
- Hardware includes gaskets and 10-32 screws

## HY-W



- Chrome-plated steel cap
- Welded
- Black powder coated finish option
- Filtration rating of 40µm (standard) / 10µm (optional)
- Air flow up to 25 cfm (750 lpm)
- Metal strainer (standard)
- Hardware includes gaskets and 10-32 screws

## HY-A



- Aluminum die-cast construction
- Filtration rating of 40µm (standard) / 10µm (optional)
- Air flow to 25 cfm (750 lpm)
- Standard 4" metal strainers (6" and 8" options available)
- Hardware includes gaskets and 10-32 screws

## TANK ACCESSORIES

## HY-AH



- Sturdy aluminum die-cast construction
- Filtration SS 100 mesh (standard)
- For rugged applications
- Standard metal strainer included
- Dipstick (optional)
- Hardware includes gaskets and 10-32 screws

## HYM



- Plastic breather for mobile applications
- Filtration rating of 10µm (standard)
- Air flow of up to 25 cfm (750 lpm)
- Rugged nylon housing
- Filler strainer with basket
- Hardware includes gasket
- Splash guard feature (standard)

## PT



- Chrome-plated steel cap
- Black powder coated finish option
- Filtration rating of 40µm (standard) / 10µm (optional)
- Air flow of up to 25 cfm (750 lpm)

## TANK ACCESSORIES

## HYC



- Weld-on filler breather
- Filtering basket
- Air filtration rating of 40µm
- Zinc-coated metal strainer
- Aluminum cap
- High-neck phosphated tube

## LEVEL GAUGE - HL91S



- O-ring type construction
- Three sizes for bolt centre (3", 5" or 10")
- For non-pressurised tanks only
- Can be mounted on tapped holes
- Suitable for mineral- and petroleum-based oils
- Maximum temperature: 80 °C (176 °F)

## TANK ACCESSORIES

## LEVEL GAUGE - LS



- Easy to install
- Thermometer included
- Easy to read
- Chrome-plated steel case
- Two sizes for bolt centre (3" or 5")
- Suitable for mineral- and petroleum-based oils

## ELECTROMAGNETIC LEVEL GAUGE - ELG



- Stainless steel rod can be cut with ease
- Suitable for unclean liquids
- Electromagnetic
- Totally safe, containing no electrical part in the fluid
- Nylon glass body


## SIGHT GLASS - SGP



- Shock-resistant
- Transparent polyamide lens
- Operating temperature: 80 °C (176 °F)
- Buna-N seal
- For use with mineral- and petroleum-based fluids
- Any contact with alcohol and/or solvents must be avoided

Series	Weld flange to suit
SGP-SAE8	TWF-OB
SGP-SAE10	TWF-OD

## STEEL SIGHT GLASS - SGS



- Shock-resistant
- Operating temperature: 80 °C (176 °F)
- Buna-N seal / dowty seal
- For use with mineral- and petroleum-based fluids

Series	Weld flange to suit
SGS-SAE6	TWF-OA
SGS-SAE8	TWF-OB
SGS-SAE10	TWF-OD
SGS-SAE12	TWF-OF
SGS-SAE16	TWF-OG
SGS-SAE24	TWF-OH

## TANK ACCESSORIES

## WELDABLE FLANGE - TWF-NPT



- Steel construction (SS available)
- Black phosphate finish (suitable for welding)
- Flanged design minimizes warpage

Series	Threads NPT
TWF-NC	3/8
TWF-ND	1/2
TWF-NE	3/4
TWF-NF	1
TWF-NG	1-1/4
TWF-NH	1-1/2
TWF-NL	2
TWF-NN	3

## MAGNETIK TANK CLEANER - MTC



- No moving parts
- Decreases wear on pumps/valves
- Eliminates troublesome ferrous fines
- Keeps hydraulic fluid cleaner
- Easy to remove without downtime or oil loss
- Improved performance when used with diffuser
- Large, exceptionally efficient large ceramic magnets

## TANK ACCESSORIES


## WELDABLE FLANGE - TWF-SAE



- Steel construction (SS available)
- Black phosphate finish (suitable for welding)
- Flanged design minimizes warpage
- SAE O-ring ensures leak protection

Series	Threads SAE
TWF-OZ	4
TWF-OA	6
TWF-OB	8
TWF-OC	10
TWF-OD	12
TWF-OE	14
TWF-OF	16
TWF-OG	20
TWF-OH	24
TWF-OI	32
TWF-OJ	48

## TANK COVER - THY



- Steel clean-out covers
- 5 models available
- Buna lip seal
- Heavy-duty steel construction